



Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Date of issue: 05/09/2018

Revision date: 05/09/2018

Version: 1.0

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Trade name : Acrytol Mounting Medium
Product code : 3801700, 3801705, 3801720, 3801721

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : To use when mounting coverglass on top of a prepared specimen
Restrictions on use : Other uses

1.4. Supplier's details

Leica Microsystems Pty Ltd
Suite 2, Level 3, Building A, Talavera Road
Macquarie Park - 2113 Australia

1.5. Emergency phone number

| Organisation/Company | Emergency number |
|--|------------------|
| ChemTrec | 800-424-9300 |
| International Calls (call collect) | +1 703-527-3887 |
| Australia 24 Hr Poisons Information Centre | 13 11 26 |

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 1 H224

2.2. Label elements

Signal word (GHS-AU) : Danger
Hazard statements (GHS-AU) : H224 - Extremely flammable liquid and vapour
Precautionary statements (GHS-AU) : P210 - Keep away from heat, sparks, open flames, hot surfaces. No smoking.
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P370+P378 - In case of fire: Use dry chemical, foam, or water spray for extinction.
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container in accordance with all local/regional/national/international regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

| Name | CAS-No. | Compound type | % | Classification according to the model Work Health and Safety Regulations (WHS Regulations) |
|--------------------------|----------|---------------|------|--|
| Toluene | 108-88-3 | | < 60 | Not classified |
| Dibutyl Phthalate | 84-74-2 | | < 10 | Not classified |
| Butylated hydroxytoluene | 128-37-0 | | < 5 | Not classified |

Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Symptoms caused by exposure

| | |
|-------------------------------------|--------------------------------------|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------------|--------------------------|
| Other medical advice or treatment | : Treat symptomatically. |
|-----------------------------------|--------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
|------------------------------|--|

5.2. Special hazards arising from the substance or mixture

| | |
|-------------|---------------------------------------|
| Fire hazard | : Highly flammable liquid and vapour. |
|-------------|---------------------------------------|

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

| | |
|----------------------|---|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. |
|----------------------|---|

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|---|
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. |
|-------------------------|---|

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

| | |
|-------------------------------|--|
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. |
| Hygiene measures | : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--------------------|--|
| Technical measures | : Ground/bond container and receiving equipment. |
| Storage conditions | : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

| Dibutyl Phthalate (84-74-2) | | |
|-----------------------------|--------------------------------|---|
| USA - ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ (Dibutyl phthalate; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| USA - ACGIH | Remark (ACGIH) | Testicular dam; eye & URT irr |

Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| Butylated hydroxytoluene (128-37-0) | | |
|-------------------------------------|--------------------------------|--|
| USA - ACGIH | ACGIH TWA (mg/m ³) | 2 mg/m ³ (Butylated hydroxytoluene (BHT); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor) |
| USA - ACGIH | Remark (ACGIH) | URT irr |

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment
Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Colour : Colourless
Odour : Pungent
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : Not applicable
Boiling point : No data available
Flash point : 44 °F / 6°C
Auto-ignition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative density : No data available
Density : 0.93
Solubility : No data available
Log Pow : No data available
Viscosity : No data available
Explosive properties : No data available
Explosive limits : No data available
Minimum ignition energy : No data available
Fat solubility : No data available

SECTION 10: Stability and reactivity

Reactivity : Highly flammable liquid and vapour.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.
Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 11: Toxicological information

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| Dibutyl Phthalate (84-74-2) | |
|-----------------------------|------------------------|
| LD50 oral rat | > 5000 mg/kg (Rat) |
| LD50 dermal rabbit | > 20900 mg/kg (Rabbit) |
| LC50 inhalation rat (mg/l) | > 15 mg/l/4h (Rat) |

| Butylated hydroxytoluene (128-37-0) | |
|-------------------------------------|--|
| LD50 oral rat | 890 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; >6000 mg/kg bodyweight; Rat) |
| LD50 dermal rat | > 2000 mg/kg (Rat; Literature study; OECD 402: Acute Dermal Toxicity; >2000 mg/kg bodyweight; Rat; Experimental value) |

| | |
|-----------------------------------|------------------|
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |

| Acrytol Mounting Medium | |
|-------------------------|------|
| Density | 0.93 |

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

| | |
|--------------------------|---|
| Ecology - general | : Harmful to aquatic life with long lasting effects. Harmful to aquatic life. |
| Acute aquatic toxicity | : Not classified |
| Chronic aquatic toxicity | : Not classified |

12.2. Persistence and degradability

| Dibutyl Phthalate (84-74-2) | |
|---------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Photolysis in the air. |
| Biochemical oxygen demand (BOD) | 0.43 g O ₂ /g substance |
| ThOD | 2.24 g O ₂ /g substance |
| BOD (% of ThOD) | 0.19 |

| Butylated hydroxytoluene (128-37-0) | |
|-------------------------------------|--|
| Persistence and degradability | Not readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photooxidation in the air. |
| Biochemical oxygen demand (BOD) | 0.51 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.27 g O ₂ /g substance |
| ThOD | 2.977 g O ₂ /g substance |
| BOD (% of ThOD) | 0.17 |

12.3. Bioaccumulative potential

| Dibutyl Phthalate (84-74-2) | |
|-------------------------------|-----------------------------------|
| BCF fish 1 | See section 12.1 on ecotoxicology |
| BCF fish 2 | See section 12.1 on ecotoxicology |
| BCF other aquatic organisms 1 | See section 12.1 on ecotoxicology |

Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| Dibutyl Phthalate (84-74-2) | |
|-------------------------------|---|
| BCF other aquatic organisms 2 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | High potential for bioaccumulation (Log Kow > 5). |

| Butylated hydroxytoluene (128-37-0) | |
|-------------------------------------|--|
| BCF fish 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Potential for bioaccumulation ($500 \leq \text{BCF} \leq 5000$). |

12.4. Mobility in soil

| Dibutyl Phthalate (84-74-2) | |
|-----------------------------|-----------------------------------|
| Surface tension | 0.034 N/m (20 °C) |
| Log Pow | See section 12.1 on ecotoxicology |

| Butylated hydroxytoluene (128-37-0) | |
|-------------------------------------|---|
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Ecology - soil | May be harmful to plant growth, blooming and fruit formation. |

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (IMDG) : 1866
UN-No. (IATA) : 1866

14.2. Proper Shipping Name - Addition

Proper Shipping Name (IMDG) : RESIN SOLUTION
Proper Shipping Name (IATA) : RESIN SOLUTION

14.3. Transport hazard class(es)

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (IMDG) : II
Packing group (IATA) : II

Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available

Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

Not applicable

Transport by sea

UN-No. (IMDG) : 1866
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : B
Flash point (IMDG) : 44F
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

UN-No. (IATA) : 1866
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchemcode : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 05/09/2018

Classification:

| | |
|--------------|------|
| Flam. Liq. 1 | H224 |
|--------------|------|

Full text of H-statements:

| | |
|--------------|---------------------------------------|
| Flam. Liq. 1 | Flammable liquids, Category 1 |
| H224 | Extremely flammable liquid and vapour |

Acrytol Mounting Medium

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS Australia Leica

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product