# Living up to Life



# **Safety Data Sheet**

Eosin 515 Lt

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND COMPANY

1.1 Product Identifier

 Trade Name
 Eosin 515 Lt

 Product #
 3801619

 SDS #
 169

SDS Date August 22, 2013

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

**Product Use**: Routine hematoxylin and eosin staining

Uses Advised Against: All other uses.

1.3 Details of the Supplier of the Substance or Mixture

Manufacturer/Preparer: Leica Biosystems Richmond, Inc. Leica Biosystems Canada, Inc.

5205 Route 12 83 Terracon Place

Richmond, IL 60071 Winnipeg, Manitoba R2J 4B3

800-225-8867 800-665-7425

1.4 Emergency Telephone Number

Emergency Spill Information 1-800- 424-9300 (CHEMTREC)

+1-703-527-3887 International calls (call collect)

Other Product Information: 1-800-225-8867

# **SECTION 2: HAZARDS IDENTIFICATION**

# 2.1 Classification of the Substance or Mixture

# CLP/GHS Classification (1272/2008):

Physical:	Health:	Environmental
Flammable Liquid Category 2	Specific Target Organ Toxicity -	Not Hazardous
	Single Exposure Category 1	
	Skin Irritant Category 2	
	Eye Irritant Category 2A	

EU Classification (67/548/EEC): F, Xn, Xi, R11, R36/38, R68/20/21/22

#### 2.2 Label Elements

DANGER! Contains methanol.







## Hazard Phrases

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H370	Causes damage to nervous system and eyes.

# Precautionary Phrases

Precautionary Prin	dses
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measure against static discharge.
P260	Do not breathe vapors.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves, protective clothing and eye protection.
P303 + P361 +	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P353	
P332 + P313	If skin irritation occurs: Get medical attention.
P305 + P351 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
P338	and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P307 + P311	IF exposed: Call a doctor or physician.
P370 + P378	In case of fire: use dry chemical, foam or water spray for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of container to approved disposal site.

## 2.3 Other Hazards: None

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1 Substances

Chemical Name	CAS Number / EINECS Number / REACH Reg. Number	% (w/w)	EU Classification (67/548/EEC)	CLP/GHS Classification (1272/2008)
Ethanol	64-17-5 200-578-6	<70	F R11	Flammable Liquid Category 2 (H225)
Isopropanol	67-63-0 200-661-7	<5	F, Xi R11, R36, R67	Flammable Liquid Category 2 (H225) Eye Irritation Category 2A (H319) Specific Target Organ Toxicity – Single Exposure Category 3 (H336)
Methanol	67-56-1 200-659-6	<5	F, T R11, R23/24/25, R39/23/24/25	Flammable Liquid Category 2 (H225) Acute Toxicity Category 3 (H301, H311, H331) Specific Target Organ Toxicity – Single Exposure Category 1 (H370)
Acetic Acid	64-19-7 200-580-7	<3	C R10, R35	Flammable Liquid Category 3 (H226) Skin Corrosive Category 1A (H314) Eye Damage Category 1 (H318)

See Section 16 for full text of GHS and EU Classifications.

www.LeicaBiosystems.com

## **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of First Aid Measures

First Aid

Eye contact: Immediately flush eye with water for at least 15 minutes while lifting the upper and lower lids.

Get medical attention if irritation persists.

Skin contact: Wash thoroughly with soap and water. Get medical attention if irritation develops. Remove

contaminated clothing and launder before reuse.

Inhalation: Remove victim to fresh air. Get medical attention if irritation persists. If breathing is difficult have

qualified individual administer oxygen and get immediate medical attention. If breathing stops,

give artificial respiration and get immediate medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. If the victim is

conscious and alert, have them rinse their mouth with water. Never give anything by mouth to

an unconscious or drowsy person. Get immediate medical attention.

See Section 11 for more detailed information on health effects.

4.2 Most Important symptoms and effects, both acute and delayed: Causes eye, and skin irritation. May cause respiratory irritation. Inhalation of vapors may cause abdominal pain and nervous system effects including dizziness, drowsiness, nausea, vomiting, visual disturbances and unconsciousness. Harmful or fatal if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed: Immediate medical treatment is required for ingestion.

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1 Extinguishing Media:

Use dry chemical, alcohol-resistant foam, carbon dioxide (CO2), or water spray.

# 5.2 Special Hazards Arising from the Substance or Mixture

Unusual Fire and Explosion Hazards: Highly flammable liquid and vapor. Vapors are heavier than air and will travel along surfaces to remove ignition sources and flash back. Vapors will collect in low areas. Vapors may be ignited by static sparks. Flames may be invisible in daylight.

Combustion Products: Oxides of carbon, smoke.

5.3 Advice for Fire-Fighters: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Wear appropriate protective equipment. Eliminate all ignition sources and ventilate the area with explosion-proof equipment. Prevent entry into basements or confined areas.

#### 6.2 Environmental Precautions:

Prevent entry in storm sewers and waterways. Report spill as required by local and federal regulations.

www.LeicaBiosystems.com

#### 6.3 Methods and Material for Containment and Cleaning Up:

Stop spill at the source if it is safe to do so. Absorb with an inert material. Use non-sparking tools and equipment. Collect into a suitable container for disposal.

#### 6.4 Reference to Other Sections:

Refer to Section 8 for personal protective equipment and Section 13 for disposal information.

# **SECTION 7: HANDLING and STORAGE**

#### 7.1 Precautions for Safe Handling:

Avoid eye and skin contact. Avoid breathing vapors. Use only with adequate ventilation. Wash thoroughly after handling. Remove contaminated clothing and launder before re-use. Keep product away from heat, sparks and all other sources of ignition. Electrically bond and ground transfer equipment, Use appropriately rated electrical equipment in areas where this material is handled and stored. Keep containers closed when not in use.

#### 7.2 Conditions for Safe Storage, Including any Incompatibilities:

Keep product away from heat, sparks and all other sources of ignition. Electrically bond and ground transfer equipment, Use appropriately rated electrical equipment in areas where this material is handled and stored.

Protect containers from physical damage. Store in a cool area. Keep away from excessive heat and open flames. Keep containers closed when not in use. Store away from oxidizers.

Empty containers retain product residues. Do not cut, weld, braze, etc. on or near empty containers. Follow all SDS precautions in handling empty containers

# 7.3 Specific end use(s): Industrial uses: None identified Professional uses: Biological stain

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 Control Parameters:

Chemical Name	US OEL	EU IOEL	UK OEL	Germany OEL
Ethanol	1000 ppm TWA OSHA PEL	None Established	1000 ppm TWA	500 ppm TWA
	1000 ppm STEL ACGIH TLV			1000 ppm STEL
Acetic Acid	10 ppm TWA OSHA PEL	10 ppm TWA	10 ppm TWA	10 ppm TWA
7.00.07.010	10 ppm TWA , 15 ppm STEL		15 ppm STEL	20 ppm STEL
	ACGIH TLV			
Isopropanol	400 ppm TWA OSHA PEL	None Established	400 ppm TWA,	200 ppm TWA,
	200 ppm TWA, 400 ppm STEL		500 ppm STEL	400 ppm STEL
	ACGIH TLV			
Methanol	200 ppm TWA OSHA PEL	200 ppm TWA	200 ppm TWA,	200 ppm TWA,
	200 ppm TWA, 250 ppm STEL	skin	250 ppm STEL	800 ppm STEL
	skin ACGIH TLV			

Refer to local or national authority for exposure limits not listed above.

Chemical Name	Biological Limit Value		
Ethanol	None Established		
Acetic Acid	None Established		
Isopropanol	Acetone in urine 40 mg/L, end of shift at end of workweek (ACGIH)		

Methanol

Methanol in urine 15 mg/L, end of shift (ACGIH)

#### 8.2 Exposure Controls:

Recommended Monitoring Procedures: Collection on charcoal tubes with analysis by gas chromatography.

**Appropriate Engineering Controls:** Use with adequate local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion-proof equipment where required.

#### **Personal Protective Measurers**

Eye/face Protection: Wear safety glasses or chemical goggles.

Skin Protection: Impervious clothing as needed to avoid skin contact.

Hands: Impervious gloves recommended (butyl or nitrile rubber).

**Respiratory Protection:** None needed with adequate ventilation. If the occupational exposure limit is exceeded, use an approved supplied air respirator. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 or other applicable regulations and good Industrial Hygiene practice.

Other protection: Suitable washing facilities should be available.

# SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### 9.1 Information on basic Physical and Chemical Properties

Appearance: Red liquid
Odor Threshold: 180 ppm Ethanol
Melting/Freezing Point: -54.1℃ (-65.4°F)
Flash Point: 17.8 ℃ (64年) (Closed Cup)

Lower Flammability Limit: 3.3% Upper Flammability Limit: 19% Vapor Density(Air=1): 1.88 Solubility: Soluble in water

Autoignition Temperature: 362°C (685°F)

Viscosity: Not established

Oxidizing Properties: None Molecular Formula: Mixture

Odor: Alcohol odor pH: 4.5 – 5.5

Boiling Point: 78.3°C (173年) Evaporation Rate: Not determined Vapor Pressure: 97 mmHg @ 20℃

Relative Density: 0.79

Octanol/Water Partition Coefficient: Not available Decomposition Temperature: Not established Explosive Properties: Vapors may be explosive in

confined areas.

Specific Gravity (H<sub>2</sub>O= 1): 0.79 Molecular Weight: Mixture

**9.2 Other Information:** None available

# **SECTION 10: STABILITY and REACTIVITY**

10.1 Reactivity: This material is not reactive under normal conditions.

10.2 Chemical Stability: Normally stable.

10.3 Possibility of Hazardous Reactions: Reaction with strong oxidizers will generate heat and cause fire.

**10.4 Conditions to Avoid:** Avoid heat, sparks, flames, and all other sources of ignition.

**10.5 Incompatible Materials:** Oxidizing agents, strong acids and bases.

**10.6 Hazardous Decomposition Products:** Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: oxides of carbon.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on Toxicological Effects:

#### **Potential Health Effects:**

**Eye Contact:** Causes irritation with redness, tearing and swelling.

Skin contact: Causes irritation and dryness. Repeated exposure may cause dermatitis. May be harmful if absorbed

through the skin.

**Inhalation:** May cause respiratory tract irritation and central nervous system effects such as dizziness,

drowsiness, nausea, vomiting, visual disturbances and unconsciousness.

**Ingestion:** Swallowing may cause gastrointestinal effects including abdominal pain, nausea and diarrhea and

central nervous system effects including dizziness, drowsiness, nausea, vomiting, visual disturbances

and unconsciousness. May cause permanent blindness.

#### Acute toxicity:

Ethanol: LD50 oral rat 7060 mg/kg; LC50 inhalation rat 20000 ppm/10 hr.

Acetic Acid: LD50 oral rat 3.31 g/kg, LD50 dermal rabbit 1060 mg/kg, LD50 inhalation rat 11.4 mg/kg/4 hr.

Isopropanol: LD50 oral rat 5045 mg/kg; LD50 dermal rabbit 12,800 mg/kg;

Methanol: LD50 oral rat 5628 mg/kg; LC50 inhalation rat 64000 ppm/4 hr; LD50 dermal rabbit 15,800 mg/kg

Skin corrosion/irritation: No data available for mixture. Acetic acid at less than 10% is slightly irritating to rabbit skin.

**Eye damage/ irritation:** No data available for mixture. Components are damaging to eyes.

**Respiratory Irritation:** No data available for mixture. High concentrations of vapors may be irritating to the respiratory system.

Respiratory Sensitization: No data available for mixture. None of the components are respiratory sensitizers.

Skin Sensitization: No data available for mixture. None of the components are skin sensitizers.

Germ Cell Mutagenicity: No data available for mixture. None of the components are germ cell mutagens.

**Carcinogenicity:** No data available for mixture. None of the components of this product are listed as carcinogens by OSHA, ACGIH, IARC, NTP, or the EU Dangerous Substances Directive. Ingestion of alcoholic beverages is known to cause cancer in humans (IARC group 1).

**Reproductive Toxicity:** No data available for mixture. Ethanol is known to cause developmental toxicity when intentionally ingested during pregnancy.

## **Specific Target Organ Toxicity:**

Single Exposure: Methanol has been found to cause visual and nervous system damage in studies with humans and animals.

Repeat Exposure: Ethanol when consumed as a beverage has been found to cause damage to the liver, nervous system and reproductive system.

# **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1 Toxicity:

Ethanol: LC50 rainbow trout 13000 mg/L/96 hr; LC50 daphnia magna 9268-14221 mg/L/48 hr; EC50 Chlorella pyrenoidosa (Green algae; growth inhibition) 9310 mg/L/48 hr

Acetic Acid: LC50 Pimephales promelas (Fathead minnow) 79 mg/L/96 hr

Isopropanol: LC50 fathead minnows 11,130 mg/L/48 hr; LC50 brown shrimp 1400 mg/L/48 hr Methanol: LC50 fathead minnows 29,400 mg/L/96 hr; EC50 daphnia magna >10,000 mg/L/24 hr

- **12.2 Persistence and degradability:** Ethanol, methanol and isopropanol are readily biodegradable in screening tests. A large number of biological screening studies have determined that acetic acid biodegrades readily under both aerobic and anaerobic conditions.
- **12.3 Bioaccumulative Potential:** Ethanol and isopropanol have an estimated BCF of 3 and methanol an estimated BCF of <10 suggesting that the potential for bioaccumulation is low. Acetic acid has an estimated BCF of 3.12.
- 12.4 Mobility in Soil: Ethanol, methanol, acetic acid, and isopropanol are expected to have very mobility in soil.
- 12.5 Results of PVT and vPvB assessment: Not required.
- 12.6 Other Adverse Effects: No data available.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste Treatment Methods:

Dispose in accordance with local, state and national regulations.

## **SECTION 14: TRANSPORTATION INFORMATION**

	14.1 UN Number	14.2 UN Proper Shipping Name	14.3 Hazard Class(s)	14.4 Packing Group	14.5 Environmental Hazards
US DOT	UN1987	Alcohols, n.o.s. (ethanol, methanol)	3	П	No
Canadian TDG	UN1987	Alcohols, n.o.s. (ethanol, methanol)	3	П	No
EU ADR/RID	UN1987	Alcohols, n.o.s. (ethanol, methanol)	3	П	No
IMDG	UN1987	Alcohols, n.o.s. (ethanol, methanol)	3	Ш	No
IATA/ICAO	UN1987	Alcohols, n.o.s. (ethanol, methanol)	3	П	No

14.6 Special Precautions for User: None

14.7 Transport in Bulk According to Annex III MARPOL 73/78 and the IBC Code: Not determined.

#### **SECTION 15: REGULATORY INFORMATION**

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

#### INTERNATIONAL INVENTORIES

**EPA TSCA INVENTORY**: All of the components are listed on the TSCA inventory.

**CANADIAN ENVIRONMENTAL PROTECTION ACT**: All of the ingredients are listed on the Canadian Domestic Substances List.

**EUROPEAN UNION:** All of the components of this product are listed on the European Inventory of New and Existing Chemical Substances (EINECS) inventory.

AUSTRALIA: All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances (AICS).

CHINA: All of the ingredients are listed on the Chinese chemical inventory.

KOREA: All of the components of this product are listed on the Korean Existing Chemical List (KECL).

NEW ZEALAND: All of the components of this product are listed on the New Zealand Inventory of Chemicals (NzloC).

PHILIPPINES: All of the components of this product are listed on the Philippine Inventory of Chemicals and Chemical Substances (PICCS).

#### **U.S. REGULATIONS**

OSHA HAZARD CLASSIFICATION: Flammable, Irritant, Target Organ Effects

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

CERCLA Section 103: The RQ for the product, based on the RQ for Methanol (5% maximum) of 5000 lbs, is 100,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 311 HAZARD CLASSIFICATION: Acute Health, Chronic Health, Fire Hazard

EPA SARA 313: This product contains the following chemicals that are regulated under SARA Title III, section 313: Methanol 67-56-1 <5%

CALIFORNIA PROPOSITION 65: This product contains the following chemicals which are known to the State of California to cause cancer, reproductive toxicity or birth defects (developmental toxicity): Methanol <5% (Reproductive).

#### INTERNATIONAL REGULATIONS

WHMIS CLASSIFICATION: Class B-2, Class D-2-B

# **SECTION 16: OTHER INFORMATION**

Revision History: Updated Logo and website.

EU Classes and Risk Phrases for Reference (See Sections 2 and 3)

F Highly Flammable

T Toxic

Xi Irritant

Xn Harmful

C Corrosive

R10 Flammable

R11 Highly Flammable

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R35 causes severe burns

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed

R67 VAPOURS may cause drowsiness and dizziness.

R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed

CLP/GHS Classification and H Phrases for Reference (See Section 3)

H225 Highly flammable liquid and vapour.

www.LeicaBiosystems.com

#169

Page 8 of 9 Issue Date: 22 August 2013 Rev F

H226 Flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to nervous system and eyes.

NFPA Rating: Health: 2 Fire: 3 Instability: 0 HMIS Rating: Health: 2 Fire: 3 Physical Hazard: 0

This Safety Data Sheet has been prepared in accordance with the REACH regulation in the EU and the Globally Harmonized System for the Classification and Labeling of Chemicals (GHS). It complies with the requirements of the Canadian Controlled Products Regulations and US 29CFR 1910.1200. To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries makes any warranty of merchantability or any other warranty, expressed or implied, which respect to such information, and we assume no liability resulting from its use. In no event shall Leica Biosystems be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages resulting from use of or reliance upon this information.